

# Hardware Reference Designs

## for SBC8260 ATM

**Wind River**

*Reference designs*

### Reference platform for preproduction design, prototyping, and evaluation

Wind River's SBC8260 ATM reference design is a single board computer (SBC) that allows development to begin before the hardware is available. This board offers a solid platform for both hardware and software engineers to use in evaluating and prototyping designs that closely parallel their final applications. The SBC8260 ATM also gives software engineers a live target on which to begin developing and testing application code.


Like all Wind River's reference designs, the SBC8260 ATM comes with detailed schematics, board support package (BSP), visionBOOT boot loader, user documentation, and power supply.

The SBC8260 ATM employs the MPC8260 (PowerQUICC II™)-Motorola's latest high-end communications chip, featuring a high-speed PowerPC EC603e core and communications engine with the ability to process protocols at up to 710 megabits per second.

Wind River's SBC8260 ATM comes standard with 64MB of SDRAM and 4MB of flash. It is user expandable to 256MB of SDRAM and 16MB of flash. The SBC8260 ATM also has access to all of the processor's communications channels via industry standard headers and connectors.

### Features

- 4MB flash (expandable up to 16MB)
- 64MB SDRAM (expandable up to 256MB)
- 8KB EEPROM controlled by CS5
- 2 communications ports (SMC1, SMC2)
- 10BaseT Ethernet on SCCI
- 10/100BaseT Ethernet on FCC2
- All CPM signals available on 3 DIN connectors
- Status LEDs, switches and controls
- 1MB on-board flash controlled by CS6
- 16MB SDRAM on local bus controlled by CS4
- visionBOOT boot loader
- VxWorks board support package
- Mictor headers for 60x bus and local bus Trace with LA Trace
- Multi-PHY ATM
- Dual SC fiber optic connections





### **Emulators for turnkey development**

visionICE II and visionPROBE II JTAG emulators are designed to handle the full lifecycle of an embedded project. These tools offer JTAG-preconfigured hardware diagnostic tests, which are crucial for hardware bring-up phases. The features and fast download speed of visionICE II and visionPROBE II help shorten software engineers' projects.

### **visionBOOT**

visionBOOT provides boot loading that can use TFTP downloading of an image from a flash file system, an HTTP server, or a disk. The flash file image includes a VxWorks image and a diagnostic script that can be used to test the board hardware. visionBOOT is built with the visionWARE software development suite, which can be purchased separately.

visionWARE automatically generates visionBOOT and diagnostics and can program flash and field programmable gate arrays (FPGAs).

### **Chip upgradability**

The 8260 processor is mounted on a BGA-to-PCA socket/adaptor, which makes the chip easily removable and interchangeable.

### **ATM SAR driver (optional)**

The ATM SAR driver is used to configure and control the CPM for AAL0, 1, 2, and 5. It can support multi-PHY and multi-Utopia bus (FCC1 and 2), has master-slave implementation, and supports both interrupt and polled modes.

## **EMBEDDED DEVELOPMENT SOLUTIONS**

### **Fully integrated solutions**

Wind River offers fully integrated hardware and software solutions designed for all phases of embedded development, from early board bring-up to debug and production/test. This tool suite includes reference designs with schematics and BSPs, software debuggers, hardware-assisted on-chip debuggers, compilers, and other software tools.

### **Hardware-assisted tools**

Wind River's JTAG emulator tools include a high-performance debugging parallel cable for PCs (visionPROBE II) as well as a networked emulator complete with 10/100BaseT capabilities (visionICE II) for both PC and UNIX.

### **Hardware tools benefits**

- Real-time target control via on-chip debugging
- High-speed binary downloads to target
- Built-in hardware diagnostics
- Flash memory programming
- Source-level debugging
- Statistical performance analysis
- Internal register configuration

### **Tornado integration**

visionICE II and visionPROBE II are tightly integrated with the Tornado® development environment and enable core and optional Tornado tools to communicate with the target through JTAG. This provides board bring-up and debug support, crash diagnosis, as well as a fast download and debug channel, if Ethernet or serial channels are used.

### **RTOS independent**

Wind River provides an extensive line of embedded development tools for all embedded real-time operating systems (RTOSs) including in-house RTOSs, Wind River RTOSs, and other commercial embedded operating systems. Published application program interfaces (APIs) support easy integration of Wind River tools with other embedded operating systems.

### **Source-level debuggers**

Fully integrated with Wind River's hardware-assisted tools are source-level debuggers including visionCLICK, visionXD, and SingleStep™ with vision running on Windows and UNIX development hosts. In addition to point-and-click capability for major functions, these debuggers offer support for hardware, software, and complex breakpoints, a register configuration utility, built-in diagnostics, and complete run control.

### **Software tools benefits**

- Intuitive graphical user interface
- Easy project configuration that reduces project start-up time
- RTOS API kit allows choice of third-party tools
- Tight integration with Wind River's full suite of embedded development tools
- Powerful register configuration utility to reduce register programming time
- Sophisticated compiler optimization technology with finegrained compiler control
- Kernel awareness for task-aware debugging of VxWorks, proprietary operating systems, and many third-party operating systems

### **The visionWARE developers kit**

Wind River's visionWARE developers kit is designed for engineers developing software that interacts with and controls hardware. visionWARE extends JTAG emulator features with an application development framework that automatically generates a boot loader and a flash file system for custom boards that store and launch customer applications. It also generates a ready-to-run diagnostics program and target resident code to program advanced programmable devices, such as flash and FPGA, using a target Ethernet port.

**Wind River Worldwide Headquarters**

500 Wind River Way  
Alameda, CA 94501 USA  
Toll free 1-800-545-WIND  
Phone 1-510-748-4100  
Fax 1-510-749-2010  
Inquiries@windriver.com  
Nasdaq: WIND

For additional contact information,  
please see our Web site at [www.windriver.com](http://www.windriver.com).

Tornado, SingleStep, VxWorks, Wind River, and the Wind River logo are trademarks, registered trademarks, or service marks of Wind River Systems, Inc. All other names mentioned are trademarks, registered trademarks, or service marks of their respective companies. Printed on recycled paper.

©2001 Wind River Systems MCL-DS-26A-0108