

```
-- file XrefJournalDefs.Mesa
-- last modified by Satterthwaite, August 26, 1977 10:47 PM
```

DIRECTORY

```
BcdDefs: FROM "bcddefs",
SymDefs: FROM "symdefs";
```

```
  XrefJournalDefs: DEFINITIONS =
BEGIN
VersionID: WORD = 08127;
XRJHeader: TYPE = RECORD[
xrefVersion: WORD,
dataOffset: CARDINAL,
sourceFile: POINTER TO StringBody, -- relative pointers
objectFile: POINTER TO StringBody,
objectVersion: BcdDefs.VersionStamp]; -- unique BCD id
PhraseIndex: TYPE = CARDINAL;
ReferenceNumber: TYPE = [0..8192);
RefData: TYPE = RECORD[
symbol: SymDefs.ISEIndex, -- identifier semantic entry index
whereReferenced: PhraseIndex,
-- character index of beginning of phrase where symbol is referenced
refTag: RefType,
sequenceNumber: ReferenceNumber];
RefType: TYPE = {
declaration, -- symbol is declared here
mention,
implicit, -- implicit use of symbol due to OPEN
lhs, -- previous mention of this ISEIndex was left hand side
address}; -- previous mention of this ISEIndex was @ operand
END.
```