```
-- File: DebugCacheDefs.Mesa
-- Last edited by
--                  Johnsson; August 29, 1978  11:04 AM

DIRECTORY
  SegmentDefs: FROM "segmentdefs" USING [FileHandle],
  VMMapLog: FROM "vmmaplog" USING [Descriptor, Entry, PilotFID];

DebugCacheDefs: DEFINITIONS =
  BEGIN

  -- VM Map and Log
  BadMapLogEntry: SIGNAL;
  InitMapSeg: PROCEDURE [SegmentDefs.FileHandle];
  LongWRITEClean: PROCEDURE [LONG POINTER, UNSPECIFIED];
  LookupMapEntry: PROCEDURE [mempage: CARDINAL]
    RETURNS [POINTER TO VMMapLog.Entry];
  NewPilot31Segment: PROCEDURE [
    vda: CARDINAL, fileid: VMMapLog.PilotFID, filepage: CARDINAL]
    RETURNS [POINTER];
  ProcessMapLog: PROCEDURE [LONG POINTER TO VMMapLog.Descriptor];
  ReinitMap: PROCEDURE [LONG POINTER TO VMMapLog.Descriptor];
  ReleaseMap: PROCEDURE;
  SwappedIn: PROCEDURE [mempage: CARDINAL] RETURNS [BOOLEAN];
  WritePilot31Page: PROCEDURE [
    address: POINTER, vda: CARDINAL,
    fileid: VMMapLog.PilotFID, filepage: CARDINAL];

  END...
```